

PUF (Poly-Urethane Foam) Monitor in Ambient Air

TE-1000

PUF for Pesticide Particulate/Vapor Air Sampler: Complete with outdoor anodized aluminum PUF shelter, aluminum blower motor assembly, 4" particulate/vapor sampling module, flow venturi calibration valve system, 0–100" magnehelic gage, motor voltage control/elapsed time indicator, 10' exhaust hose, and 7-day mechanical timer(110V/60hz or 220v/50hz)

Meets EPA Methods TO4A, TO9A, TO13

SPECIFICATIONS:

Flow rate:	200-280 lpm (7-10cfm)
Filter media:	4" round microquartz filters (TE-QMA4)
Flow control:	Motor speed control/ elapsed time indicator (TE-5010)
Motor blower	2-stage vacuum 0.6 HP 110v/60hz (TE-116336) 220v/50hz (TE-116125)
Flow Indicator:	0-100" magnehelic gage (TE-1005)
Timer:	7-day mechanical timer (TE-5007)
Elapsed time indicator device:	Elapsed time indicator (TE-5012)
Sampling module:	Particulate/vapor sampling module with Tischalloy® coating (TE-1002)



Shipping Information:

Size/Weight: 45.5" x 22.5" x 20" /70 lbs.
19" x 14" x 14" /9 lbs.

Other electrical characteristics available



Anchor International 4 Boulder Lane Horsham, PA 19044 USA

Tel: 215 674 0111 Fax: 215 674 0112

Email: info@anchor-intl.com